



**→** Ø7.2 **→** 



3.13 -Ø PER-ORDER SHAFT LENGTH PER ORDER **ADJUSTABLE** Ø PER-

**ORDER** 





OPTIONAL AIR MOTOR INCLUDES MUFFLER AND NEEDLE VALVE. REFER TO TABLE FOR AIR SUPPLY REQUIREMENTS.

## NOTES:

- CLAMP AND MOUNTING PLATE MOUNTS PROVIDE 20° ANGULAR OFF-CENTER MOUNTING AND 0° TO 60° VERTICAL ADJUSTMENT.
- ALL DIMENSIONS IN INCHES.

AIR MOTOR HORSEPOWER				
AND AIR CONSUMPTION				
HORSEPOWER	1/2	1		
CFM AIR	23	40		
CONSUMPTION	25			
AT PSI	40	80		
INLET SIZE (NPT)	3/8	3/8		

*WEIGHT IS IN POUNDS WITH ELECTRIC MOTOR. DOES
NOT INCLUDE SHAFT OR IMPELLER(S) OR AIR MOTOR.
THIS IS A MAXIMUM WEIGHT. ACTUAL WEIGHT
DEPENDS ON SPECIFIC MOTOR TYPE AND SELECTION.

MIXER	DIMENSION		
MODEL	Α	В	*WGT
MD33	17.3	11.2	43
MD50	18.2	11.2	50
MD75	18.6	11.2	53

 $^{\star}$  ALL DIMENSIONS AND WEIGHTS ARE FOR REFERENCE ONLY UNLESS THE DRAWING IS CERTIFIED.

\* ALL EQUIPMENT DESIGN AND APPLICATION DATA SHOWN HEREIN IS CONFIDENTIAL AND THE PROPERTY OF BRAWN MIXER. NO USE OR DISCLOSURE THEREOF MAY BE MADE WITHOUT OUR WRITTEN PERMISSION.

DRAWN BY:BSB DATE:9/25/2018 © 2018 APPROVED BY: DATE:



MIXER MODEL **MD33 THRU 75** 

DIMENSION AND ASSEMBLY DRAWING

TK0130

DWG. B-PH: 616-399-5600 FAX: 616-399-3084